

ABSA TARGET PACKAGE

Distances are in yards and accurate to within + or - 3 yards

(To determine target distances in meters, multiply yardage x 0.914)

Target designators, distances, sizes & shapes:

A - 323 (8" Sq.)

B - 335 (40% IPSC, 12" sq.)

C - 498 (12" Sq.)

D - 511 (40% IPSC, 66% IPSC)

E - 528 (66% IPSC, 12" Diamond w/ 10" tangents, 10" Sq., 50% IPSC)

F - 530 (10" Sq., 12" Sq.)

G - 535 (66% IPSC)

H - 650 (66% IPSC, 16" Sq.)

I - 685 (16" Sq.)

J- 718 (A1st Target / 18" Sq. body w/ 12" Rd. head)

K - 768 (22" Diamond w/ 16" tangents)

L - 794 (16" Sq., 12" Sq., 10" Sq., 8" Sq.)

M – 815 -819 (12" Turkey, 66% IPSC, 12" Circle)

N - 827 - 831 (24" Turkey, 66% IPSC, 16" Sq.)

O - 852 - 854 (18" W x 24" L Rect., 16" sq., 12" sq.)

P - 857 (66% IPSC, 32" W x 91/2" L Rect.) / Stacked Vertically

Q - 864 (12" Sq.)

R – 862 - 864 (22" Diamond w/ 16" tangents, 8" Sq.)

S - 866 (18" W x 24" L Rect.)

T - 880 (22" Diamond w/16" tangent, 66% IPSC)

U- 1107 (32" x 16" Ram, Full IPSC, 66% IPSC, 50% IPSC, 34" x 9" Coyote, 24" x 6" Coyote, 12" Circle, 32" x 16" Ram)



Magnum Approved Targets / Shapes, Rules, Locations:

- **IPSC Shaped Targets (example above) beyond 500 yards are “Magnum Rated”.**
- **Except for Designator “U”, only IPSC’s can be engaged with Magnum Calibers.**
- **No Targets of any kind inside of 500 Yards are to be engaged with Magnum Calibers.**
- **IPSC Percentage/Size Breakdown in Inches:**
 - Full IPSC (Body = 18” W x 24” L / Head = 6”x 6”)
 - 66% IPSC (Body = 11-3/4” W x 15-1/2” L / Head = 4”x 4”)
 - 50% IPSC (Body = 9” W x 12” L / Head = 3”x 3”)
 - 40% IPSC (Body = 8-1/2” W x 10-1/2” L / Head = 2-1/2”x 2-1/2”)
- **Any Target at Designator U may be engaged with Magnum Calibers.**
- **Magnum Target Locations / Designators:**
 - **D** (40% IPSC, 66% IPSC)
 - **E** (66% IPSC, 50% IPSC)
 - **G** (66% IPSC)
 - **H** (66% IPSC)
 - **M** (66% IPSC)
 - **N** (66% IPSC)
 - **P** (66% IPSC)
 - **T** (66% IPSC)
 - **#9** (Full IPSC, 66% IPSC)
 - **#10** (Full IPSC)
 - **U** (Ram, Full IPSC, 66% IPSC, 50% IPSC, Ram)

Truing Lane Notes:

- **Truing Bar locations are designated as follows.**
 - **The number on the Blue and Yellow Designator equals the distance as denoted below.**
 - **3 = 300 yards, 6 = 600 yards, 7 = 700 yards, 8 = 800 yards, etc.**
 - **Truing Lane goes incrementally from 300-1000 yards.**
 - **Total of 8 “Truing” locations spaced every 100 yards.**
- **Most Truing Bars are accurate to within + or - 1 yd of their designated range, except the following:**
 - 400 Truing Bar is – 413
 - 500 Truing Bar is – 503
 - 900 Truing Bar is – 905
- **All other Truing Bars are accurate to within + or - 1 yd.**
- **Truing target sizes.**
 - **There are 2 sizes of targets at each truing location.**
 - **Each truing location has a 10“x 10“square target.**
 - **Each truing location also has a “T” target that is .2 Milliradian (.7 MOA) tall.**